



- for smooth and embossed non-woven wallpapers and for non-woven woodchip wallpapers
- for direct wall application with roller
- instant: ready-for-use in 5 minutes
- with extra-strong methylcellulose and adhesion promoters

Roller Adhesive for non-woven wallpapers PREMIUM

Use

Adhesive is ideal for bonding non-woven wallpapers by wall-pasting method (adhesive application to wall). Also for bonding heavy wall coverings, e.g. textile, glassfibre fabrics, embossed, vinyl wallpapers and the like, by traditional method (adhesive application to wallpaper).

Constituents

Methyl cellulose, polyvinyl acetate powder, adhesion promoters

Substrate

Substrate shall be dry, strong and free from adhesion-impairing substances (e.g. grease, dust, mould oil). Remove existing badly adhering wallpaper and distempers with **baufan® Wallpaper Remover**. Repair cracks and holes with **baufan® Indoor Filler** or **decomur Super Bonding Filler**. Pretreat highly absorbent, friable and chalking substrates with **baufan® Deeply Penetrating Primer** – solvent-free. For translucent wallpapers (particularly in case of differently coloured substrates), pretreatment with **baufan® Wallpaper Primer white** is recommended.

Application

Stirring vigorously, briskly sprinkle **baufan® Roller Adhesive** into cold water and briefly continue to stir (see table for mixing ratio). Stir again vigorously after 5 minutes.

Application to substrate:

As non-woven wallpapers require no softening time, they can be quickly and easily applied by wall-pasting method. To do this, apply prepared adhesive uniformly to substrate with short-pile roller or brush over a width equivalent to 1 - 2 wallpaper strips. Place wallpaper strip directly into freshly placed adhesive and press down evenly to remove entrapped air.

Application to wallpaper:

Apply adhesive uniformly to wallpaper and place coated faces against each other. After adequate soaking time, hang wallpaper strips with butted seams and press down. Observance of wallpaper manufacturer's application guidelines is essential. Immediately remove any adhesive residue on front face of wallpaper with wet cloth.

Mixing ratio

Mixing ratio	Water quantity	Coverage
Application to substrate: * Non-woven wallpapers / glassfibre wallpapers poly-laminated		
1 : 15	3 ltr	15 – 20 m ²
Application to wallpaper: * Vinyl wallpapers / heavy wallpapers * Glass fabric / textile wallpapers		
1 : 20	4 ltr	20 – 25 m ²

Swelling time

Ready to use in 5 minutes

Consumption

200 – 300 ml/m²

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 48 months from production date (see batch label).

Item No.

102367

200 g

Folding box

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.