



- synthetic resin-reinforced
- high bond strength, dries to transparent finish
- for woodchip and heavy wallpapers
- free from preservatives

# Wallpaper Adhesive Special

### Use

For bonding all kinds of wallpaper, including woodchip, embossed, vinyl, photographic and special wallpapers.

### Constituents

Methyl cellulose, starch ether, polyvinyl acetate powder and additives

### Substrate

Substrate shall be dry, clean, strong, absorbent, smooth and free from adhesion-impairing substances. Strip existing wallpaper with **baufan® Wallpaper Remover** or **baufan® Wallpaper Power Remover**. Repair cracks, holes and uneven surfaces with **baufan® Indoor Filler**. Pretreat friable and chalking substrates with **baufan® Deeply Penetrating Primer – solvent-free**. Apply preliminary adhesive coat to highly absorbent substrates (mixing ratio 1:40) or pretreat with **baufan® Deeply Penetrating Primer – solvent-free**.

### Application

Stirring vigorously, briskly sprinkle pack contents into cold water (see table) and briefly continue to stir. Restir prepared mix vigorously after approx. 30 minutes. Apply adhesive uniformly to wallpaper strips, place coated faces against each other and allow to soak. After recommended soaking time, hang wallpaper strips with butted seams and press down evenly with paperhanging brush, roller or spatula to remove entrapped air. Observance of wallpaper manufacturer's application guidelines is essential. Wash tools with fresh water after use.

### Mixing ratio

Mixing ratio	Water quantity	Coverage
Pre-pasting:		
1 : 40	8.0 ltr	60 – 80 m <sup>2</sup>
Woodchip / heavy wallpapers:		
1 : 20	4.0 ltr	22 – 26 m <sup>2</sup> = 5 rolls
Special bonding / unprinted embossed wallpapers:		
1 : 15	3.0 ltr	10 – 15 m <sup>2</sup> = 2 - 3 rolls

For very heavy wallpapers or low-suction substrates and to increase moisture resistance, addition of one (750 g) pot of **baufan® Wall Covering Adhesive** per pack of **Wallpaper Adhesive Special** is recommended. This is stirred into ready-mixed adhesive.

### Swelling time

Approx. 30 minutes

### Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

### Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

### Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 48 months. Production date: see batch label.

### Item No.

102350

200 g

Folding box

### Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.