

- white marking paint with very good opacity
- for temporary marking of sports pitches and lawns
- rainproof, quick-drying
- suitable for all standard marking equipment

Sports Pitch Marking

Use

As temporary line marking on sports pitches, natural lawn areas, hard (tennis) courts etc., with excellent adhesion to air-dry grass and good visibility in rain.

Constituents

Copolymer dispersion, polymer thickener, extra-finely graded mineral fillers, titanium dioxide, water, additives

Substrate

For natural lawn areas, sports pitches, hard (tennis) courts. Surfaces for spraying shall be dry.

Application

Do not mix Sports Pitch Marking with other paints. Stir well prior to use. Carefully mix with required quantity of water. **baufan**[®] Sports Pitch Marking can be diluted with up to 5 parts water. The less water, the higher the paint luminosity. Please perform trial marking to determine optimum mixing ratio. Apply paint by pressure spraying using suitable marking equipment. Diluted product shall be applied promptly due to risk of sedimentation. Carefully wash marking machine/spray nozzle with clear water immediately after use (continue spraying until water is clear).

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. For spray application, use combi-filter A2/P2.

Mixing ratio

Recommendation:

- First marking ▶ 1 : 3
- Second marking ▶ 1 : 5

Consumption

Per football pitch, undiluted → approx. 2 – 3 kg
(Empirical values) = 3.0 – 3.5 g/m for 10 cm width

Consumption is dictated by nature of ground, mixing ratio and user's working procedure.

Application temperature

+5 °C for material, ambient air and substrate

Drying time

Approx. 2-5 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Tinting

If necessary, tintable with max. 5 % suitable emulsion, full-tone and tinting paints (solvent-free).

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Refrain from eating, drinking and smoking while using paint. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal product (preservative):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

Item No.

103777 14.0 kg PE canister

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.