

- pure white, high-opacity, high coverage
- set to sprayable consistency, quick-drying
- rainproof

Sports Pitch Marking - Direct

Use

As temporary line marking on sports pitches, natural lawn areas, hard (tennis) courts etc., with excellent adhesion to air-dry grass and good visibility in rain.

Constituents

Copolymer dispersion, cellulose thickener, extra-finely graded fillers and pigments (titanium dioxide), water, additives

Substrate

For natural lawn areas, sports pitches and hard (tennis) courts. Surfaces for spraying shall be dry. Grass should be cut as short as possible.

Application

Do not mix baufan® Sports Pitch Marking with other paints. Paint is supplied ready-for-use. Stir well prior to use. Apply paint in undiluted form by pressure spraying using suitable marking equipment. Carefully wash marking machine/spray nozzle with clear water immediately after use (continue spraying until water is clear).

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. For spray application, use combi-filter A2/P2.

Consumption

Per football pitch \rightarrow approx. 8.0 - 12.0 kg (Empirical values) = 12 g/m for 10 cm width

Consumption is dictated by nature of ground and user's working procedure.

Application temperature

+5 °C for material, ambient air and substrate

Drying time

Approx. 2-5 hours under normal conditions (at \pm 20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Tinting

With Universal Concentrated Colorants or Full-Tone and Tinting Paint.

Note

Mask areas not to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Refrain from eating, drinking and smoking while using paint. Wear goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal product (preservative):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

GISCODE for coating materials: BSW20 EU VOC limit value for this product: (Cat.: A/a, Wb) = 30 g/ltr (2010) Max. VOC content of this product: 1 g/ltr

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

Item No.

103784 12.5 kg PE canister

Status: August 2020 Page 1 of 1