



- high penetration depth
- odourless, concentrated surfactant solution
- fast and easy removal of woodchip and other wallpapers

Wallpaper Remover

Use

baufan[®] Wallpaper Remover is ideal for easy removing paper-backed, textile, vinyl and woodchip wallpapers and distemper finishes.

Constituents

Non-ionic surfactant, water and additives

Substrate

For paper-backed, textile, vinyl and woodchip wallpapers and distemper finishes. Prior to treatment, roughen waterproof and coated wallpaper with needle roller or coarse sandpaper.

Application

Dilute baufan[®] Wallpaper Remover with water.

Mixing ratios:

- lightweight/medium-heavy wallpapers, glues:

250 ml/15 ltr water

- heavy wallpapers:

250 ml/8-10 ltr water

Hot water will enhance stripping performance.

Mask areas (floors, doors and furniture) not to be treated.

Apply solution generously with brush or suitable spray equipment (do not inhale spray mist) and allow to work for 5-15 minutes, depending on wallpaper type. If necessary, repeat application. Prior to treatment, roughen waterproof wallpapers and painted woodchip wallpaper with needle roller or coarse sandpaper. Mechanically strip softened wallpaper and glue, using spatula for best results. Wash tools with fresh water immediately after use.

To remove distemper finishes, apply baufan[®] Wallpaper Remover (250 ml diluted with 10 ltr water) to surface, allow to work for short time, then scrape off with spatula. Remove any residue by washing down. Wallpaper Remover is neutral, stains can be easily removed with water. Subsequent bonding is not impaired.

Consumption

250 ml suffice for approx. 35 – 50 m² (depending on dilution).

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Note

Keep out of reach of children. Ensure adequate ventilation during application. Do not inhale spray mist. Refrain from eating, drinking and smoking during use. Avoid contact with skin and eyes. In case of contact with eyes or skin, rinse immediately with plenty of water. Spray application shall only be performed by trade applicators. Hand over only fully emptied containers for recycling.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 60 months from production date (see batch label).

Item No.

102237

1.0 ltr

PE bottle

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.