

- optimum substrate preparation prior to wallpapering
- produces homogeneously white and uniformly absorbent substrates with good key
- ideal for non-woven wallpapers, solvent-free

Wallpaper Primer white

Use

baufan® Wallpaper Primer white is excellently suited for evening out colour differences in substrate prior to wallpapering. It is applied in single operation to produce homogeneously white and uniformly absorbent substrate with good key. Ideal for all wallpapers – especially light-coloured and translucent non-woven wallpapers. Also suitable for renovation works requiring white substrate, e.g. for floated plasterwork indoors.

Constituents

Synthetic resin dispersion, titanium dioxide, mineral components, water, additives

Substrate

Suitable for all mineral substrates (e.g. concrete, gypsum plaster, cement render and lime render), firmly adhering emulsion paint coats and gypsum plasterboard and other drylining board.

Substrate shall be dry, solid, strong, level and free from dust and grease. Remove loose material and badly adhering coatings from substrate. Prime highly absorbent, friable and chalking substrates with baufan® Deeply Penetrating Primer – solvent-free. Remove existing wallpaper and distemper finishes with baufan® Wallpaper Primer. Repair cracks, holes and irregularities with suitable baufan® filler.

Application

Stir well prior to use and apply with roller, brush or suitable spray equipment (maximum aggregate size is 0.2 mm). Allow substrate pretreated with baufan® Wallpaper Primer white to fully dry prior to performance of any subsequent works. Wash tools with water after use.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. For spray application, use combi-filter A2/P2.

Consumption per coat

Smooth surfaces/fine plaster aggregate → from 100 – 200 ml/m²

Exact consumption rate to be determined by trial application on site.

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 6-8 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Tinting

With max. 10 % Universal Concentrated Colorants or Full-Tone and Tinting Paint.

Note

Surfaces painted with Wallpaper Primer white shall not be overcoated over larger areas with gypsum-bearing filling compounds. A dispersion-based filling compound (e.g. baufan® Ready-Mix Filler or baufan® Multi-Purpose Filler) is recommended in such cases to guarantee optimum adhesion. Mask areas not to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Refrain from eating, drinking and smoking while using paint. Wear goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

Product Code: M-GP01

EU VOC limit value for this product:

(Cat.: A/a, Wb) = 30 g/ltr (2010)

Max. VOC content of this product: 1 g/ltr

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

Item No.

102039	2.5 ltr	PE tub
102084	5.0 ltr	PE tub
102091	10.0 ltr	PE tub

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.