

- high coverage, strong bond
- yellowish granulate, odourless
- for normal and lightweight paper-backed wallpapers

Wallpaper Adhesive

Use

For bonding lightweight and normal paper-backed wallpapers. Cement- and lime-resistant.

Constituents

Starch ether, cellulose ether and additives

Substrate

To achieve optimum bond, substrate shall be dry, strong and free from dust and grease. Remove existing badly adhering wallpaper and loose coatings with baufan® Wallpaper Remover.

Pretreat high-suction substrates with baufan® Deeply Penetrating Primer – solvent-free or apply preliminary adhesive coat with baufan® Wallpaper Adhesive (mixing ratio 1:80).

Application

Stirring vigorously, sprinkle wallpaper adhesive into cold water and briefly continue to stir. Restir vigorously after 30 minutes to produce ready-to-use adhesive. Apply adhesive uniformly to wallpaper, place coated faces against each other and allow to soak. After adequate soaking time, hang wallpaper as normal with butted seams. Observance of wallpaper manufacturer's application guidelines is essential.

Immediately wash off adhesive residue with water.

Mixing ratio

Mixing ratio	Water quantity	Coverage
Pre-pasting:		
1 : 65	8 ltr	50 – 60 m ²
Normal wallpaper:		
1 : 50	5 - 6 ltr	30 – 35 m ² = 6 – 7 rolls

Solubility

Ready to use in 30 minutes

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 48 months from production date.

Item No.

102305

125 g

Folding box

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.