

- ready-to-use, for wall-pasting
- for smooth and embossed non-woven wallpapers and for non-woven woodchip wallpapers
- no splashing or dripping
- high initial adhesion and bond strength, easy to correct, dries to transparent finish

# Roller Adhesive for non-woven wallpapers ready-to-use

## Use

Adhesive is excellently suited for bonding non-woven wallpapers and other dimensionally stable wall coverings. Associated wall-pasting technique involves application of adhesive to substrate with suitable roller and direct placement of wall covering into adhesive bed. This allows simple and neat bonding of dimensionally stable wall coverings.

## Constituents

Methyl cellulose, synthetic resin dispersion, additives, water

## Substrate

Substrate shall be dry, clean, strong, level, uniformly absorbent, and free from dust and grease. Remove existing wallpaper and badly adhering coatings. Repair cracks, holes and irregularities with **baufan**<sup>®</sup> Indoor Filler. Prime highly absorbent, friable and chalking substrates with **baufan**<sup>®</sup> Deeply Penetrating Primer – solvent-free. For bonding translucent non-woven wallpapers to non-uniformly coloured substrates, pretreatment with **baufan**<sup>®</sup> Wallpaper Primer white is recommended.

## Application

### Wall-pasting method (application to substrate)

As non-woven wallpapers require no softening time, they can be quickly and easily applied by wall-pasting method. To do this, evenly apply adhesive to substrate with short-pile roller over a width equivalent to 1 – 2 wallpaper strips. Place wallpaper strip into freshly placed adhesive and press down evenly to remove entrapped air. Open time of adhesive is approx. 10 to 15 minutes and applies for a building fabric and room temperature of approx. + 20 °C, 50-70 % relative humidity and moderately absorbent substrates.

### Application to wallpaper:

Apply adhesive uniformly to wallpaper with pasting brush and place wallpaper with butted joints, as specified by manufacturer. Immediately remove any adhesive escaping at seams using clean, damp cloth.

Overcoatable wall coverings shall only be overcoated after adhesive has fully dried.

Wash tools with water after use.

Observance of wallpaper manufacturer's application guidelines is essential.

## Consumption

Approx. 200 g/m<sup>2</sup>

Contents suffice for approx. 5 Euro rolls = approx. 25 m<sup>2</sup> (Euro roll = approx. 10.05 m x 0.53 m)

## Drying time

Approx. 24 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

## Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

## Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

## Contains biocidal product (preservative):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

## Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 36 months from production date (see batch label).

## Item No.

103227

5.0 ltr

PE tub

## Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.