

- grey, also adheres to wet substrates
- crack-bridging up to 10 mm, permanently elastic
- immediately waterproof – irrespective of weather

Water Stop

Use

This product is suitable for rapid repair of leaks in roofs, patios, masonry etc.

Constituents

Alkyd resin, polyacrylic fibres, fillers, solvents, additives

Substrate

baufan[®] Water Stop adheres to all standard construction materials, e.g. bitumen, roof tiles, roofing felt, aluminium, copper, zinc, concrete, clay bricks/blocks, tiles, wood, etc.

Substrate shall be strong and free from adhesion-impairing substances. Mechanically remove soiling, loose masonry, moss and other growth. Stabilize any inadequately strong substrates, e.g. friable, crumbling plaster/render with baufan[®] Deeply Penetrating Primer – solvent-free.

Application

baufan[®] Water Stop is supplied ready-for-use and shall not be diluted. Product may be applied with brush or spatula. When applying, ensure that surface is properly sealed and min. 2 mm coat thickness is achieved. Where applied to moist substrate or in poor weather conditions (low temperatures, rain etc.), apply a second coat at latest after one week. Overcoating with acrylic coatings is possible after 24 hours. Clean tools after use.

Consumption

Approx. 1.5 kg/m²

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Approx. 24 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate).

Relative humidities exceeding 90%, particularly in conjunction with low temperatures, may considerably influence drying time and quality features.

Note



Warning

Flammable liquid and vapour. May cause drowsiness or dizziness. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames. No smoking. Avoid breathing vapours. Repeated exposure may cause skin dryness or cracking.

Wear protective gloves/eye protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If medical advice is needed, have product container or label at hand. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local/regional/national special waste disposal regulations. Contains: naphtha (crude oil).

ADR/GGVSE transport regulations: UN 1866, 640E, Class: 3, Cl. code: F1, Packing group: III; LQ7

Product not subject to ADR transport regulations as it has flash point above 23°C, is transported in containers smaller than 450 ltr and has flow time exceeding 40 sec. (Section. 2.2.3.1.5.)

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: 48 months from production date (see batch label).

Item No.

128022	750 ml	Metal can
--------	--------	-----------

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.