

Wallpaper Adhesive - Normal Normalkleister

High quality methyl cellulose wallpaper adhesive

Instructions for use: *Wallpaper Adhesive - Normal* is suitable for hanging light to medium-weight wallpapers.

Technical specifications:

Components:	methyl cellulose, starch ether
Density:	approx. 0.40 g/cm ³
pH-value:	approx. 8
Solubility:	ready for use in 30 minutes
Usage:	approx. 200 ml/m ²

Surface preparation: The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using *PUFAS Wallpaper Remover*. Make good cracks and holes using *PUFAS Interior* or *PUFAMUR Super Bonding Filler*. Pretreat highly absorbent, sanding and chalking surfaces using *PUFAS Deeply-Penetrating Primer – solvent free*.

Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *PUFAS Insulating Spray White*.

We recommend applying a sub-coat of *PUFAS Wallpaper Primer- White* before hanging highly translucent wallpapers and where surfaces are highly contrasting.

Application: Stirring vigorously, sprinkle *PUFAS Wallpaper Adhesive – Normal* into clean, cold water and continue to stir for a few minutes. Leave for 30 minutes and then stir vigorously again.

Evenly apply *PUFAS Wallpaper Adhesive – Normal* to the wallpaper fold the pasted ends inwards and hang after an adequate soaking time. Hang the wallpaper according to the manufacturer's instructions.

Do not use if the surface and room temperature are below + 5° Celsius!
Remove adhesive residues using a damp cloth.
Clean tools in water after use.

Mix ratio:

for	Mixing ratio	Quantity of water per 125 g packet	Coverage of a 125 g packet
Pre-pasting	1:80	10	60-80 m ²
Lightweight wallpapers	1:70	8 3/4	50 m ²
Medium-weight wallpapers	1:60	7 1/2	40 m ²
Heavy wallpapers	1:50	6 1/4	30 m ²

Storage: Store in a cool and dry place!

Available size: 125 g collapsible box 000101000