

Decorative Effect Plaster – fine

Use:

Decorative Effect Plaster – fine is a ready-to-use mineral-based decorative quartz and is suitable for all mineral substrates, gypsum plasterboard and drylining board and emulsion paint coats indoors.

Properties:

- fine surface texture
- easy application with roller or brush
- aggregate size 0.5 mm
- opaque white finish
- highly water vapour-permeable
- free from preservatives, solvents and plasticizers
- tintable

Technical data:

Raw material base: Mineral components, potassium water glass, polymer dispersion, titanium dioxide, water and additives

Density: Approx. 1.66 g/cm³

pH value: Approx. 11

GISSCODE (German hazardous substances classification) for coating materials: BSW10

Substrate preparation:

Substrate shall be dry, clean, solid, strong and free from adhesion-impairing substances. Pretreat highly absorbent, friable and chalking substrates with high-quality primer. Repair cracks, holes and irregularities with suitable filler.

Application:

Stir well prior to use and apply with brush or roller. Drying time is approx. 8 – 12 hours, though depends on ambient temperature and humidity.

Tinting:

For colour finishes, Decorative Effect Plaster – fine can be tinted with max. 5 % PUFAMIX/decomix Concentrated Colorants.

Overcoatability:

Decorative Effect Plaster – fine can serve as decorative finishing coat, though, if required, may also be overcoated with suitable emulsion paints.

Consumption:

1 kg suffices for approx. 1.8 – 2.5 m² for single coat, depending on substrate suction and texture.

Note:

Do not use at building fabric and ambient temperatures below +5 °C. Wash tools with water immediately after use. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with water. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at www.decotric.de or from sds@decotric.de.

EU VOC limit value for this product (Cat.: A/a, Wb) = 30 g/ltr (2010). Max. VOC content of this product: 1 g/ltr.

Storage and disposal:

Store in cool, though frost-free environment in properly sealed containers, out of reach of children. Hand over only fully emptied containers for recycling.

Item No.	EAN	Container size
060502301	4007955605027	8 kg
060503301	4007955605034	15 kg



Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.