

Technical Information Sheet

Effect Glazes

Effektlasuren

Glaze for a modern interior design

Instructions for use:	A glaze on acrylate basis with a modern brighter effect that change depending on the light. Suitable for ceilings and wall coatings on wallpapers, colours, brick, masonry, finery, Styrofoam and similar interior surfaces. The acrylic gets transparent after drying and only the glitter remains visible.	
Technical specifications:	Components:	Styrol-Acrylic- Dispersion, effect pigments, additive
	Density:	approx. 1.05 g/ml
	pH-value	7-8
	Usage:	80-120 ml/m ² per coat
Surface preparation:	The surface must be dry, firm and free of release agents (dust, formwork release oil, etc.). Do not apply <i>decotric Effect Glaze</i> until the wallpaper has completely dried.	
Application:	Shake well before use! <i>decotric Effect Glaze</i> is ready to use and can be applied using a paint roller, brush or spreader. Do not use if the surface and/or room temperature are below + 5° C. Clean tools in water immediately after use.	
Storage:	Store in a cool, but frost-free place. Keep the containers tightly sealed.	
Article No.:	791 Pearl Effect	017003001
	792 Brilliant Effect	017103001
	793 Diamont Effect	017303001
	794 Rubin Effect	017203001
	(750ml, 1,5l)	
	795 Smaragd Effect (750)	017503001
	796 Saphir Effect(750)	017403001
Available size:	1.5 l PP tin	