

- for normal and heavy wallpapers, medium viscosity
- high coverage, even on rough substrates
- high bond strength, stain-free drying

Extra Wallpaper Adhesive Economy Pack

Use

For bonding lightweight to heavy wallpapers etc.

Constituents

Starch ether, rheological additives

Substrate

For substrates such as plaster, render, concrete, gypsum, gypsum plasterboard etc. Substrate shall be dry, clean, smooth, strong and free from adhesion-impairing substances (e.g. grease, dust, mould oil). Completely remove distemper finishes, wallpaper residue and loose coatings. Fill holes and irregularities with **baufan® Indoor Filler** and smooth down. Pretreat highly absorbent and friable substrates with **baufan® Deeply Penetrating Primer – solvent-free**. (Pretreat rough plasters with **baufan® Liquid Lining Paper**.)

Application

Stirring, sprinkle pack contents into cold clean water (see table for mixing ratio) and briefly continue to stir. Allow prepared mix to stand for approx. 30 minutes, then restir vigorously. Apply adhesive to cut-to-size wallpaper strips, place coated faces against each other and, after adequate soaking time, hang with butted seams. For heavy wallpapers or low-suction substrates and to increase moisture resistance, add a 750 ml pot of **baufan® Latex Binder** or 750 g of **baufan® Wall Covering Adhesive** to 3 – 4 ltr of prepared wallpaper adhesive. Observance of wallpaper manufacturer's application guidelines is essential. Wash tools with water after use.

Consumption

Approx. 200 ml/m²

Swelling time

Ready to use after approx. 30 minutes

Mixing ratio for 500 g pack

Mixing ratio	Water quantity	Coverage
Pre-pasting:		
1 : 25	12.5 ltr	approx. 70 m ²
Lightweight paper-backed wallpapers:		
1 : 20	10.0 ltr	50 – 60 m ²
Heavy paper-backed wallpapers:		
1 : 10 to 1 : 12	5.0 – 6.0 ltr	25 – 30 m ²

Mixing ratio for 1 kg pack

Mixing ratio	Water quantity	Coverage
Pre-pasting:		
1 : 25	25.0 ltr	approx. 140 m ²
Lightweight paper-backed wallpapers:		
1 : 20	10.0 ltr	100 – 120 m ²
Heavy paper-backed wallpapers:		
1 : 10 to 1 : 12	10.0 – 12.0 ltr	50 – 60 m ²

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

Item No.

330310	500 g	Folding box
330312	1.0 kg	Folding box

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.