

- synthetic resin-reinforced, for woodchip, textured, vinyl and embossed wallpapers
- high coverage, even on rough plasters
- very high bond strength, stain-free drying

Extra Special Wallpaper Adhesive

Use

For bonding woodchip, vinyl, embossed and textile wallpapers etc.

Constituents

Synthetic resin powder, starch ether and additives

Substrate

For substrates such as plaster, render, concrete, gypsum, gypsum plasterboard etc. Substrate shall be dry, clean, strong and free from adhesion-impairing substances (e.g. grease, dust, mould oil). Completely remove distemper finishes, wallpaper residue and loose coatings. Fill holes and irregularities with filler and smooth down. Pretreat highly absorbent and friable substrates with **baufan®** Deeply Penetrating Primer – solvent-free. Pretreat rough plasters with **baufan®** Liquid Lining Paper.

Application

Stirring, sprinkle pack contents into cold clean water (see table for mixing ratio) and briefly continue to stir. Allow prepared mix to stand for approx. 30 minutes, then restir vigorously. Apply adhesive to cut-to-size wallpaper strips, place coated faces against each other and, after adequate soaking time, hang with butted seams. For heavy wallpapers or low-suction substrates and to increase moisture resistance, add a 750 ml pot of **baufan®** Latex Binder or 750 g of **baufan®** Wall Covering Adhesive to 3 – 4 ltr of prepared wallpaper adhesive. Observance of wallpaper manufacturer's application guidelines is essential. Wash tools with water after use.

Consumption

Approx. 200 ml/m²

Swelling time

Ready to use after approx. 30 minutes

Mixing ratio for 500 g pack

Mixing ratio	Water quantity	Coverage
Pre-pasting:		
1 : 20	10 ltr	approx. 70 m ²
Lightweight wallpapers:		
1 : 16	8 ltr	40 – 45 m ²
Woodchip:		
1 : 14	7 ltr	35 – 40 m ²
Vinyl and embossed wallpapers:		
1 : 12	6 ltr	30 – 35 m ²
Heavy wallpapers:		
1 : 12	6 ltr	30 – 35 m ²

Mixing ratio for 1 kg pack

Mixing ratio	Water quantity	Coverage
Pre-pasting:		
1 : 20	20 ltr	approx. 140 m ²
Lightweight wallpapers:		
1 : 16	16 ltr	80 – 85 m ²
Woodchip:		
1 : 14	14 ltr	70 – 75 m ²
Vinyl and embossed wallpapers:		
1 : 12	12 ltr	60 – 65 m ²
Heavy wallpapers:		
1 : 12	12 ltr	60 – 65 m ²

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

Item No.

330510	500 g	Folding box
330512	1.0 kg	Folding box

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.