

Painter and Repair Fabric - 10 m x 10 cm

Use:

Glassfibre non-woven for indoors and outdoors for repairing hairline cracks and crazing on walls and ceilings (crack type A.1 to BFS (German Federal Committee for Paint and Protection of Material Assets) guidance paper no. 19) as well as for various crack repairs in construction facilities. Ideal for use as scrim reinforcement for filling works to gypsum plasterboard.

Properties:

- easy workability
- water- and chemical-resistant
- for indoor and outdoor use

Technical data:

Colour: White
Weight per unit area: Approx. 35 g/m²
Thickness: Approx. 270 µm

Application:

Uniformly apply filler to substrate with notched trowel. With smooth substrates, non-woven may also be directly bonded to substrate with wallpaper or dispersion adhesive. Place Painter and Repair Fabric into material without folds/creases or entrapped air and smooth down with spatula. After full drying, pretreat repaired surface with solvent-free primer, e.g. decotric Primer – solve nt-free.

Painter and Repair Fabric may be bonded or filler-coated with butted joints or lapped joints with subsequent double-cutting.



Item No.	EAN	Size
009601000	4007954096017	10 m x 10 cm

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.