

# Metallic Paints

## Metall-Effekt-Farben

Opaque, solvent free paint for decorative covers. Acrylate base for interior use.

**Instructions for use:** *Metallic Paint* is a glaze on Acrylic basis for a modern brighter effect. Suitable for ceiling and wall coatings on wallpapers, colours, brick, masonry, finery, Styrofoam and similar surfaces.

**Technical specifications:**

Components:	Styrol-Acrylic- Dispersion, metallic pigments, additive
Density:	approx. 1.5 g/cm <sup>3</sup>
pH-value:	approx. 8-8.5
Consumption:	80-120 ml/m <sup>2</sup>

**Surface preparation:** The surface must be dry, firm and free of release agents (dust, formwork release oil, etc.) Remove all traces of loose plaster, flaking paint residues and old coats of distemper paint. Smooth over cracks and holes with *PUFAS Interior* or *Pufamur Interior Super Bonding Filler*. Prime highly absorbent, sanding and chalking surfaces using *PUFAS Deeply Penetrating Primer – Solvent Free* or *LH*.

**Application:** Shake well before use!

*Metallic Paint* is ready to use and can be applied using a paint roller, brush or spreader.

Under durable influence of moisture it can come to discolouration on painted surfaces.

Do not use if the surface and/or room temperature are below + 5° Celsius!  
Clean tools in water immediately after use.

**Storage:** Store in a cool, but frost-free place! Keep containers tightly sealed!

<b>Available sizes:</b>	750 ml	017702001	Gold Metallic
	750 ml	017802001	Silver Metallic
	750 ml	018402001	Orient gold

**Note:**

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.