

Professional Glazier's Putty

PROFI Glaserkitt

- high-quality window putty for glazing according to DIN 18545
- handy round can for stable, clean storage
- colour beige

Instructions for use:

Professional Glazier's Putty is made from natural raw materials and is ideally suited for single and repair glazing for windows with wood, steel and concrete frames.

Technical specifications:

Components: Linseed oil, Rügener natural chalk
Colour: Beige
Density: approx. 2 g/cm³
Setting time: 4-6 weeks

Substrate preparation:

The window frame must be clean, dry and free of grease. The rabbets must be primed. However, to guarantee optimum bonding of the linseed oil filler, the primer should not be applied so thick that it closes off the pores in the wood.

Application:

After kneading Professional Glazier's Putty, press firmly into the rabbet and smooth the surface using a glazing knife. It is very important that any condensation, which occurs during the drying time, is prevented from penetrating the filler bed.

As the filler needs oxygen to bond, double windows should not be assembled immediately after glazing.

After the filler has cured, after 4-6 weeks at the latest, it must be painted over with weatherproof, elastic paint. If using acrylic paints, you should always carry out preliminary tests first.

Clean tools in PUFAS Paint Brush Cleaner R120 or aka Soluwash S special cleaner immediately after use.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Clean any working equipment with water after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool, dry but frost-free place! Keep the containers tightly sealed!

Available sizes:

| | | | |
|-------|---------------|-----------|-----|
| 750 g | 4016818390680 | 059803000 | REG |
|-------|---------------|-----------|-----|