

- extra-high bond strength, high initial adhesion
- high coverage, water-thinnable
- odourless, dries to transparent finish

Wall Covering Adhesive

Use

For bonding wall and ceiling coverings indoors. Particularly suitable for use with flat and foam vinyl wallpapers as well as textile wallpapers. Do not use in spaces with higher moisture exposure.

Constituents

Synthetic resin dispersion, water, additives

Substrate

For substrates such as concrete, aerated concrete, gypsum wallboard, filling compounds, cement render, gypsum plaster, rigid-foam and wood-based panel products, existing emulsion paint coatings. Varnished substrates shall be scuff-sanded.

All substrates shall be dry, clean, level, strong, absorbent and free from adhesion-impairing substances. To increase strength, use **baufan® Deeply Penetrating Primer** – solvent-free. Completely remove any substrates that cannot be stabilized or that adhere inadequately. In case of doubt, perform trial bonding. Repair any irregularities.

Application

Stir well prior to use. Cut wallpaper to required length. Apply adhesive generously and uniformly to wall with lambskin roller over 1 – 3 strip width. Allow flash-off time of a few minutes for adhesive. Finally apply wallpaper to wall with hard rubber roller, taking care to prevent bubbles. Allow longer flash-off time in case of low-suction substrates, low temperatures or high humidity. Please observe wall covering manufacturer's application guidelines during all works. Immediately remove adhesive residue with fresh water. Wash tools with fresh water after use.

Consumption

Depending on substrate → from 200 g/m²

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Open time

Approx. 20 minutes

Correction time

Max. 15 minutes

Drying time

Approx. 24 hours under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking during application. Wear goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzoisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

Storage

Store in cool, though frost-free environment in properly sealed containers. Minimum shelf life in unopened containers subject to proper storage: see batch label.

Item No.

102664	750 g	PE pot
102671	3.0 kg	PE tub

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.