

- **all-rounder: repairing, filling and bonding**
- **rapid set in 30 minutes**
- **white, for indoor and outdoor use**

Drill Hole and Crack Filler ULTRA

Use

Special, white, rapid-set cementitious filling compound with excellent bonding and filling properties. For patching cracks and holes on virtually all substrates indoors and outdoors. Adheres even to glazed tiles. **baufan®** Drill Hole and Crack Filler ULTRA can also be used as an adhesive and repair compound.

Constituents

Special white cement, synthetic resin powder, mineral fillers and additives

Substrate

Substrate shall be dry, strong, clean and free from dust and grease. Pretreat highly absorbent, friable and chalking substrates with **baufan®** Deeply Penetrating Primer – solvent-free. Thoroughly clean and degrease tiles and other non-absorbent substrates.

Application

Mixing: Sprinkle 750 g powder into approx. 300 ml cold clean water and stir thoroughly until homogenous compound is achieved. If a higher sag resistance is required for a specific application, then reduce water quantity to 250 ml.

Application:

Apply prepared filling compound within 30 minutes. Material can even out holes/chips/spalls up to 10 cm deep in one layer in single operation. Subsequent coating and bonding shall only be performed after full drying.

Consumption per coat

Per mm application thickness → approx. 1.0 kg/m²

Application temperature

+5 °C to + 30 °C for material, ambient air and substrate

Drying time

Drying time is approx. 24 hours, depending on application thickness, substrate and ambient temperature, under normal conditions (at +20 °C, 65 % relative humidity and moderately absorbent substrate); allow suitably longer drying times for unfavourable conditions.

Note

Keep out of reach of children. Do not use at building fabric and ambient temperatures below +5 °C. Wash tools with water immediately after use. Hand over only fully emptied containers for recycling. Cured material residue may be disposed of as domestic or construction site waste. EWC waste code: 06 02 99. GHS CODE (German hazardous substances classification) ZP1. Low-chromate to Regulation (EC) No 1907/2006, Annex XVII (47).

Safety data sheet shall be observed.

Up-to-date safety data sheets are available from our website at www.baufan.de

Storage

Store in cool, though frost-free environment in properly sealed containers.

Minimum shelf life in unopened containers subject to proper storage: 48 months from production date (see batch label).

Item No.

101476	750 g	Box
--------	-------	-----

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.