



- white, waterproof
- for kitchens and bathrooms
- crack-free curing

Tile and Joint Repair

Use

Special high-grade grout for finishing joints in wall tiling. Ideal for quick repair of damaged tile joints. Allows straightforward, neat application and cures uniformly without cracking.

Constituents

Synthetic resin dispersion, mineral fillers, water, additives

Technical data

Colour:	White
Density:	Approx. 1.8 g/cm ³
pH value:	Approx. 9 - 10

Substrate

Joints shall be dry, clean and free from dust and grease. Remove loose material from joints. Mask porous and unglazed tiles prior to grouting.

Application

Knead tube well prior to use. Press **baufan**[®] Tile and Joint Repair directly into joint to be treated, ensuring that this is completely filled. Carefully remove any projecting grout (e.g. with rubber spatula) before this starts to dry. Wipe down tiles with damp sponge, then rub down to dry. Material is waterproof when fully dried.

Application temperature

Not below +5 °C for material, ambient air and substrate

Note

Keep out of reach of children. Ensure adequate ventilation during application and drying. Refrain from eating, drinking and smoking while using paint. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, sewers, surface waters or ground. Hand over only fully emptied containers for recycling.

Contains biocidal products (preservatives):

Methylchloroisothiazolinone/methylisothiazolinone (3:1), benzisothiazolinone. May cause an allergic reaction. Advice for isothiazolinone allergy sufferers is available on 0049 (0) 341 / 44655-0.

Storage

Store in cool, though frost-free environment in properly sealed tube. Keep out of reach of children. Minimum shelf life in unopened containers subject to proper storage: 36 months from production date (see batch label).

Item No.

101490	350 g	Stand-up tube
--------	-------	---------------

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.