

# Tile and Surface Filler

- for indoor use
- outstanding adhesion on difficult substrates
- also suitable for damp spaces
- very easy to sand

## Use

Synthetic resin-reinforced, fine filling compound based on special cement for indoor wall and ceiling surfaces. Ideal for patching, smoothing, filling and joint grouting. **baufan**<sup>®</sup> Tile and Surface Filler excels by its outstanding adhesion, even on difficult substrates, and may also be applied in damp spaces. Suitable substrates include painted glassfibre, glazed tiles, gypsum board, concrete, cement, clay bricks/blocks, gypsum, lime etc. Filler-coated surfaces may serve as base for paint finishes, wallpaper and plaster. Not suitable for flexible substrates.

## Constituents

Comprising: special cement, elasticizing synthetic resin, methyl cellulose, additives

Bulk density: 1 g/cm<sup>3</sup>

pH value: Approx. 11.5

## Substrate preparation

Substrate shall be dry, strong, clean and free from dust and grease. Remove loose particles, badly adhering and elastic coatings. Pretreat highly absorbent, friable and chalking substrates with **baufan**<sup>®</sup> Deeply Penetrating Primer – solvent-free. Thoroughly clean and degrease tiles and other non-absorbent substrates.

## Mixing

Sprinkle 2 parts by volume **baufan**<sup>®</sup> Tile and Surface Filler into 1 part by volume cold, clean water and stir until lump-free compound is achieved (mixing ratio: 1 kg powder + 500 ml water). Prepared filling compound is workable for approx. 40 minutes.

## Application

Apply **baufan**<sup>®</sup> Tile and Surface Filler with spatula or finishing trowel (in 0 – 20 mm coat thickness). Filling compound is easy to smooth and felt-float and, where necessary, can be readily sanded down after full drying. After sanding, sanded areas require treatment with **baufan**<sup>®</sup> Deeply Penetrating Primer – solvent-free.

## Consumption:

1 kg powder for 1 m<sup>2</sup> with 1 mm coat thickness

## Note

Do not use at building fabric and room temperatures below +5 °C. Wash tools with water after use. For repairs, take due account of differences in absorbency and alkalinity. Observance of coating and adhesive manufacturers' instructions for pretreatment of cementitious substrates is essential. Not suitable for long-term exposure to moisture.

## Storage

Store properly sealed pack in cool, dry place.

## Disposal

Hand over only fully emptied containers for recycling. Cured material residue may be disposed of as domestic or construction site waste. EWC waste code: 06 02 99.

## Item No.

103647	5 kg	Bag
--------	------	-----

## Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.