

Painters' Renovation Fabric RV 130

Special glassfibre non-woven for substrate preparation for subsequent indoor painting and wallpapering works

Use:

- For refurbishment of wall coatings
- Wide-area bridging of surface cracks
- Ideal as substrate preparation for *pufatherm* board

Technical data:

Raw material base:	Glassfibre, binders
Weight per unit area:	Approx. 132 g/m ²
Thickness:	Approx. 0.28 mm
Reaction to fire:	B1 to DIN 4102

Substrate preparation:

Substrate shall be dry, clean and strong. Remove existing wallpaper and non-adhering coatings. Pretreat highly absorbent and chalking substrates with *decotric Primer – solvent-free*. Smooth down rough substrates with filling compounds.

Application:

1. *decotric Glass Fabric and Non-Woven Adhesive GK*, *decotric Glass Fabric Adhesive GF* or *decotric Wall Covering Adhesive* is recommended for bonding. Apply adhesive to wall in strip width and embed non-woven without soaking time. Press down with suitable tool. Hang strips with butted seams.

2. Application to substrate of *decotric Styrofoam Adhesive* or *decomur Ready-Mix Filler* with C1 notched spatula is recommended to level out uneven surfaces. Then embed non-woven in adhesive/filler and press down.

Painters' Renovation Fabric RV 130 can only be bonded with butted seams.

Further works to repaired surfaces are possible after full drying.

Item No.:

9601

Container size:

Roll 10 m x 1 m