



- white silk matt for indoor use
- outstanding adhesion, non-yellowing, low-odour
- primer, finishing coat and sealer all in one

Special Tile Paint

3 in 1

Technical data

Raw material base: Special polymer dispersion, mineral components, titanium dioxide, water, additives

Use

Silk-matt water-based coating for ceramic wall tiles indoors. For direct application to tiles without sanding or additional priming. Ideal for kitchens, bathrooms and WC suites.

Substrate

Tiles shall be dry, clean and free from dust and grease. Thoroughly clean tiles with baufan Multi-Clean. Remove soap, lime and silicone residue. Repair damaged joints and plug holes with baufan Tile and Joint Repair, and allow to fully dry prior to further works. Mask adjoining surfaces, e.g. floors and sanitary appliances.

Application

Apply tile paint in two to three coats with intermediate drying using short-pile paint roller. Remove adhesive tape immediately after application. Paint is touch-dry after approx. 60 minutes and overcoatable after approx. 4-6 hours – unfavourable conditions (e.g. low temperatures or high humidity) may result in longer drying times. Paint finish is fully loadable after four days.

For colour finishes, tile paint can be tinted with max. 10 ml decomix Universal Concentrated Colorant per 750 ml pot.

Consumption

Approx. 100 ml/m². Contents suffice for approx. 7.5 m² for single coat and approx. 3.75 m² for two coats.

Note

Painted surface can be cleaned with standard, mild domestic cleaners (do not use scouring agents). Not suitable for wet spaces. Technical data sheet shall be observed. Do not use at temperatures below +8 °C. Wash tools with water immediately after use. **Warning!** Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

EU VOC limit value for this product (Cat.: A/i, Wb) = 140 g/ltr. Max. VOC content of this product: 140 g/ltr.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at www.baufan.de.

Storage

Store in cool, though frost-free environment in properly sealed containers. Keep out of reach of children.

Disposal

Hand over only fully emptied containers for recycling. Dried material residue may be disposed of as domestic or construction site waste. Dispose of uncured waste under EWC waste code: 08 01 11.

Item No.

025024

750 ml

Pot

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.